



# CALUMET

SPECIALTY PRODUCTS PARTNERS, L.P.

2780 Waterfront Pkwy, E. Dr. Suite 200 Indianapolis, IN 46214  
Phone: 317-328-5660 Fax: 317-328-5668 Sales: 1-800-437-3188 www.calumetspecialty.com

## Product Data Sheet

If you have questions regarding this product, please contact your Sales Representative.  
Customer Service and Technical Service can be reached at 1-800-437-3188

Product: **CALSOL 8120**  
Revised **06/13/2013**  
HazMat Name: **Non-Regulated**

Product Code: **2080-00-P**

<u>Test</u>	<u>UOM</u>	<u>Method</u>	<u>MIN</u>	<u>MAX</u>	<u>Typical</u>
VISCOSITY @ 40°C	cSt	D445			239.76
VISCOSITY @ 100°C	cSt	D445			13.83
VISCOSITY @ 100°F	SUS	D2161	1200.0	1400.0	1304.9
VISCOSITY @ 210°F	SUS	D2161			75.2
API GRAVITY @ 60°F		D4052	19.0	21.0	21.0
FLASH POINT, COC	°C	D92	210		221
FLASH POINT, COC	°F	D92	410		430
POUR POINT	°C	D97		-9	-12
POUR POINT	°F	D97		15	10
COLOR, ASTM		D1500		2.0	L1.0
ANILINE POINT	°C	D611	82.2	96.1	87.0
ANILINE POINT	°F	D611	180.0	205.0	188.6
NEUTRALIZATION NUMBER	mg KOH/g	D974		.030	.009
VISCOSITY-GRAVITY CONSTANT		D2501			.869
REFRACTIVE INDEX @ 20°C		D1218			1.5087

**DISTRIBUTED BY: R.E. CARROLL, INC. 1570 NORTH OLDEN AVENUE, TRENTON NJ 08638-3204 USA**  
**T: 609-695-6211/800-257-9365 F: 609-695-0102 www.recarroll.com**

Copyright 2012 Calumet Specialty Products Partners, L.P.

Calumet's sampling and testing procedures in effect at the time of production will be used for certification testing. Results may be based on tank certification, manufacturing data, periodic testing and/or most recent product restock. Results only represent the values one would expect if the product was tested in our laboratories with our test methods on the specified date. The typical values of product properties are not frequently measured and are not based on a statistically relevant number of tests. Calumet does not represent that the typical values contained on this data sheet represent the values in the product supplied to the user. The information in this document relates only to the named product. The user is solely responsible for determining the suitability of the product for its use intended by user, including use in any process and the combination of the product with any other material.