



BP Bartran HV

High viscosity index antiwear hydraulic oils

Description

The BP Bartran™ HV range of high viscosity index (VI) lubricants are based on a carefully selected ashless additive system designed to meet and exceed the most exacting performance standards.

Application

Bartran HV oils are intended for severely stressed hydraulic systems requiring a high level of antiwear performance and fine filtration. In addition, Bartran HV exhibits excellent corrosion protection as well as outstanding thermal and oxidative stability. Bartran HV has excellent hydrolytic stability and separates rapidly from water contamination.

The selection of a shear stable VI Improver ensures that there is no excessive loss in viscosity due to mechanical shearing. The VI Improver also imparts a very low pour point which enables the product to be used in very cold environments.

These grades are intended for two main types of duty:

- Outdoor plant likely to operate in wide ranges of temperature - such as machinery subjected to cold start up conditions and high temperature continuous running. Examples include off-highway and marine applications.
- Indoor manufacturing equipment that incorporates control systems requiring a hydraulic fluid whose viscosity change with temperature is minimal. Examples include precision machine tools.

The Bartran HV range is fully compatible with elastomer materials commonly used for static and dynamic seals, such as nitrile, silicone and fluorinated (e.g. Viton) polymers.

Bartran HV is classified as follows:

DIN classification – HVLP

ISO 6743/4 – Hydraulic Oils Type HV

Bartran HV grades meet the requirements (for appropriate viscosity grade) of:

DIN 51524 Part 3

Cincinnati Lamb (Milacron) (P 68-69-70)

Denison (Parker Hannafin) HF-0

US Steel 126 & 127

Eaton (formally Vickers) I-286-S & M-2950-S

Frank Mohn

Advantages

- High viscosity index and low pour point enables the product to be used over a wide temperature range, with good shear stability means no excessive loss in viscosity due to mechanical shearing.
- Excellent antiwear performance provides extended wear protection for hydraulic pumps. Reduced down time due to unscheduled maintenance and savings from reduced replacement part costs.
- Excellent water separation and hydrolytic stability means reduced down time through prolonged lubricant life and increased equipment reliability.
- Excellent thermal and oxidative stability provides reliable performance and extended oil life in severe applications. Minimal deposit formation gives a cleaner system and reduced frequency of filter changes.
- Good filterability characteristics in both wet and dry conditions enables cost savings to be made due to increased filter life.

Typical Characteristics

Test	Method	Units	15	22	32	46	68	100	150
Density @ 15°C	ISO 12185 / ASTM D4052	g/ml	0.88	0.87	0.87	0.87	0.88	0.88	0.88
K.V. @ 40°C	ISO 3104 / ASTM D445	mm ² /s	15	22	32	46	68	100	150
K.V. @ 100°C	ISO 3104 / ASTM D445	mm ² /s	3.8	4.8	6.3	8.1	10.8	13.2	17.7
Viscosity Index	ISO 2909 / ASTM 2270	-	>150	>150	>150	>150	>140	>130	>125
Pour Point	ISO 3018 / ASTM D97	°C	-48	-42	-39	-36	-36	-33	-30
Flash Point, PMC	ISO 2719 / ASTM D93	°C	144	162	186	186	192	192	192
Foam Sequence I	ISO 6247 / ASTM D892	mls/mls	20/0	20/0	20/0	20/0	20/0	20/0	20/0
Demulsification @ 54°C	ISO 6614 / ASTM D1401	mins	5	10	10	15	15	-	-
Demulsification @ 82°C	ISO 6614 / ASTM D1401	mins	-	-	-	-	-	20	20
Air Release @ 50°C	ISO / 9120 / ASTM D3427	mins	4	4	4	8	8	12	18
FZG (A8.3/90), fail stage	ISO 14635-1 / DIN 51354	-	-	-	11	12	12	12	12
Rust Test (24 hrs synthetic sea water)	ISO / 7210 / ASTM D665B	-	Pass	Pass	Pass	Pass	Pass	Pass	Pass
K.V. @ 100°C after 4 hours KRL	DIN 51350 T6	% loss	-	-	-	9.5	-	-	-

Subject to usual manufacturing tolerances.

BP, Bartran HV, and the BP logo are trademarks of BP p.l.c, used under licence

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet.

It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

BP Limited, Pipers Way, Swindon, Wiltshire SN3 1RE, UK
www.castrol.com/industrial
www.castrol.com