



## Product Data

### Enersyn SG-XP

Premium Synthetic Gear Lubricant

#### Description

BP Enersyn™ SG-XP are fully synthetic gear lubricants based on carefully selected polyglycol fluids and containing anti-oxidant, rust-inhibiting and EP additives of high thermal stability.

#### Application

The Enersyn SG-XP has inherently superior properties relative to mineral lubricants, therefore these grades are especially suitable for the high temperature lubrication of gears and bearings, particularly in large scale mills and calenders. In worm gears operating with mineral oil at low speeds and high torques, conditions of boundary lubrication tend to promote pitting and consequent rapid wear of bronze worm-wheels. Fatty oils (also known as compounded oils) were found to be effective in reducing pitting, but suffered from rapid oxidation at high running temperatures. Enersyn SG-XP grades are suitable for these applications and also allow extended drain and change intervals. Some manufacturers employ them for fill-for-life lubricants.

#### Advantages

- Reduced frictional losses leads to reduced energy consumption and lower sump temperatures.
- Higher thermal stability, hence minimal formation of sludge and deposits.
- Better load-carrying properties and reduced wear compared with conventional mineral oils.
- Inherently higher Viscosity Index (VI) which, with the lower pour point, results in a wider range of service temperatures (- 30 °C to 150 °C continuous bulk temperatures, with intermittent operating temperatures of up to 220°C)

## Typical Characteristics

Name	Method	Units	100	150	220	320	460	680
Density @ 15°C / 59°F	ISO 12185 / ASTM D4052	kg/m <sup>3</sup>	1010	1020	1020	1020	1020	1020
Kinematic Viscosity @ 40°C / 104°F	ISO 3104 / ASTM D445	mm <sup>2</sup> /s	100	159	220	320	460	680
Viscosity Index	ISO 2909 / ASTM 2270	-	217	228	200	220	235	263
Pour Point	ISO 3016 / ASTM D97	°C/°F	-45/-49	-39/-38.2	-36/-36	-36/-36	-39/-38.2	-33/-27.4
Flash Point - open cup method	ISO 2592 / ASTM D92	°C/°F	274/ 525.2	286/ 546.8	280/ 536	280/ 536	280/ 536	270/ 518
Rust test - distilled water (24 hrs)	ISO 7120 / ASTM D665A	Rating	Pass	Pass	Pass	Pass	Pass	Pass
Copper corrosion (24 hrs@100°C/212°F)	ISO 2160 / ASTM D130	Rating	1a	1a	1a	1a	1a	1a
Timken OK Load test	ASTM D2782	kg/lb	34/75	34/75	34/75	34/75	34/75	34/75
FZG Gear Scuffing test - A/ 8.3/90	ISO 14635-1	Failure Load Stage	-	>12	>12	>12	>12	>12
FZG Gear Scuffing test - A/ 16.6/140	ISO 14635-1 (modified)	Failure Load Stage	-	>12	>12	>12	>12	>12

Subject to usual manufacturing tolerances.

## Additional Information

Normal industrial paints are not compatible with these lubricants. Gearboxes should be left unpainted internally, or alternatively should be painted with two component coatings such as epoxy resins. Care must be taken that seal materials are compatible with the SG-XP lubricants. The recommended materials are nitrile rubber (NBR), fluoro-silicone rubber (FVMQ), and vinyl-methyl-polysiloxane rubber (VMQ). Incompatible materials are likely to shrink or swell, thus causing either severe leakage or seizure of the seal. These products are NOT miscible with mineral oils.

Enersyn SG-XP

21 Sep 2012

BP, the BP logo and related marks are trademarks of BP p.l.c., used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

BP Industrial , Technology Centre , Whitchurch Hill , Pangbourne , Reading , RG8 7QR , United Kingdom

[www.castrol.com/industrial](http://www.castrol.com/industrial)